Rotary Hammer

HR2670FT

800 W SDS-PLUS 26 mm 3.0 J

Model HR2670FT is compatible with SDS-PLUS bits. Has increased power and durability by the redesign of the internal structure.

This model is equipped with three operation modes, Rotation only, Hammering only, Rotation + hammering. Chuck type: Quick change chuck, High efficiency, Torque limiter, Variable speed by trigger, Reverse switch.



Technical specifications

Continuous Input Power 240V	800 W
No load speed	0 - 1500 min^{-1}
Impacts per Minute (IPM)	0 - 4500 min^{-1}
Max. Drilling Diameter in Wood	32 mm
Max. Drilling Diameter in Concrete	26 mm
Max. Drilling Diameter in Steel	13 mm
Optimum Drilling Diameter Range in Concrete	4 - 18 mm
Impact Energy	3,0 J
Drilling diameter with TCT core bit	68 mm
Adapted for SDS-PLUS bits	✓
Power Supply Cord	4,0 m
Sound Power Level (L_{WA})	102 dB(A)
Sound Pressure Level (L_{pA})	94 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)

User benefits

- One touch sliding chuck enables quick and easy bit changes
- Recessed lock-on button for continuous use
- LED light illuminates the work site

EAN 0197050007209

Link to product - www.makitauk.com

Related products

Standard AC

821925-3
Plastic Carrying Case



Optional AC

1914L8-4
Dust Cup Set



1914M0-7
Dust Cup Set



1914X3-8
Dust Collection Pad



821925-3
Plastic Carrying Case



Other

User manual

Parts drawing