TDS

MASTER MECHANIC 10 RAL PAINT



DESCRIPTION

High gloss and fast drying acrylic paint in aerosol, with high coverage and excellent adhesion. Also, the line includes metallic aerosol paint for metal surfaces which are not rub resistant and not resistant to weather influences.

PROPERTIES

- Viscosity: 18-25sec (Flow Cup DIN4, 20°C)
- Density: 0.6-0.8 g/L (Density Cup 100cm^3/20°C, ASTM D – 1475)
- VOC content : 640g/L
- Flash Point: -104°C
- Drying time
  (1 Layer, Temperature 20°C, Humidity <65%):
  Touch: 5-10min
  Through dry: 1h
  Maximum hardness: 24h
- Coverage: 5m^2/L
- Can Pressure: 4bar (20°C), 8 bar (50°C)
- Contents: 500ml

INSTRUCTIONS FOR USE

APPLICATION
Remove all dust, rust and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 25 - 30cm from the surface. Try the spray on testing surface. For better results apply 2-3 thin coats, 3-5 min apart.
Best application temperature: 10°C - 25°C.

AFTER USE
Spray holding the can inverted for 3''. Clean the caps with solvent

STORAGE
5°-35°C. Do not put in vehicles.

CAP SYSTEM



SMART CAP
- Less overspray
- Extreme Coverage
- Fast drying
- Hard chisel lines
- Even coating
- Suitably for effects
- Dual way spraying

SAFETY

Request SDS

COLOR RANGE

RAL 9010
WHITE MATTE

RAL 9010
WHITE GLOSS

RAL 9005
BLACK MATTE

RAL 9005
BLACK GLOSS

RAL 9006
SILVER

*Cap indicates the color of the can.

There are likely to be declinations in digital performance of shades.

ISSUED DATE: 21/11/2024

VERSION: 01

COSMOS LAC A.E.
PAINT INDUSTRY

©2024

1 PINDOU STR., 17672 KALLITHEA, ATHENS, GREECE
T. +30 210 95 70 222 | E. support@cosmoslac.com| W. www.cosmoslac.com
MADE IN GREECE

CERTIFIED QUALITY SYSTEM
ISO 9001