TDS

MASTER MECHANIC 04 WASH PRIMER



DESCRIPTION

Primer for difficult substrates. Provides excellent adhesion and good exterior durability. Suitable for one component (1K) coatings and primer for difficult substrates such as galvanized steel and non-ferrous metals.
Can be over painted with any colour.

PROPERTIES

- Viscosity: 18-25sec (Flow Cup DIN4, 20°C)
- Density: 0.6-0.8 g/L (Density Cup 100cm³/20°C, ASTM D – 1475)
- Flash Point: -104°C
- Drying time
  (1 Layer, Temperature 20°C, Humidity <65%):
  Touch: 5-10min
  Through dry: 1h
  Maximum hardness: 24h
- Coverage: 3m²/L
- GLOSS (GLOSS METER 60°ASTM D – 1471):
  1-3 GLOSS UNITS/MATT
- Can Pressure: 4bar (20°C), 8 bar (50°C)
- Contents: 500ml

INSTRUCTIONS FOR USE

APPLICATION
Remove all dust, rust, and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 25-30cm from the surface. Try the spray on testing surface. Apply the primer in several thin layers. For better results apply 2-3 thin coats, 3-5 min apart. **Best application temperature: 10°C - 25°C.**

AFTER USE
Spray holding the can inverted for 3''. Clean the caps with solvent

STORAGE
5°-35°C. Do not put in vehicles.

CAP SYSTEM



SMART CAP
- Less overspray
- Extreme Coverage
- Fast drying
- Hard chisel lines
- Even coating
- Suitably for effects
- Dual way spraying

SAFETY

Request SDS

COLOR RANGE

04 WASH PRIMER
LIGHT YELLOW
—

*Cap indicates the color of the can.

There are likely to be declinations in digital performance of shades.

ISSUED DATE: 21/11/2024

VERSION: 01

COSMOS LAC A.E.
PAINT INDUSTRY
©2024
1 PINDOU STR., 17672 KALLITHEA, ATHENS, GREECE
T. +30 210 95 70 222 | E. support@cosmoslac.com| W. www.cosmoslac.com
MADE IN GREECE

CERTIFIED QUALITY SYSTEM
ISO 9001